

BLANK PAGE



Indian Standard

ENGINEERING METROLOGY — ENGINEER'S PARALLELS — SPECIFICATION

(First Revision)

भारतीय मानक

इंजीनियरी माप विज्ञान — इंजीनियरी समान्तरक — विशिष्ट (पहला पुनरीक्षण)

UDC 531.717.88

© BIS 1990

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

FOREWORD

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards on 13 March 1990, after the draft finalized by the Engineering Metrology Sectional Committee had been approved by the Light Mechanical Engineering Division Council.

This Indian Standard was originally published in 1967. This first revision has been brought out to align with the technical practices prevalent in the country.

In the preparation of this standard, considerable assistance has been derived from BS 906 (Part 1): 1972 'Engineer's parallels: Part 1 Metric units' issued by the British Standards Institution (BSI).

This standard includes sizes which are best suited for the use of parallels individually or in combination thereof to cover the entire range in small increments.

Squareness accuracy for working faces has been deleted as it does not affect the performance of the parallel and the box adjustable type parallels excluded from the purview of this standard, as they are normally not used.

Indian Standard

ENGINEERING METROLOGY — ENGINEER'S PARALLELS — SPECIFICATION

(First Revision)

1 SCOPE

1.1 This standard covers the requirements for precision engineer's parallels of Grades 1 and 2, supplied always in pairs, and used in shop floor and for inspection purposes.

2 REFERENCES

2.1 The following Indian Standards are necessary adjuncts to this standard:

IS No.

Title

2102

General tolerances for dimen-(Part 1): 1980 sions and form and position: Part 1 General tolerances for

linear and angular dimensions

(second revision)

7018

Technical supply conditions for (Part 1): 1983 gauges: Part 1 General (first

revision)

3 TERMINOLOGY

3.1 For the purpose of this standard, working surfaces shall mean the four long sides of the parallel.

4 GRADES

4.1 The engineer's parallels shall be of two grades, Grade 1 for reference purposes and Grade 2 for workshop purposes.


5 DIMENSIONS AND TOLERANCES

- 5.1 Dimensions and tolerances of engineer's parallels of Grade 1 shall be as given in Table 1.
- 5.2 Dimensions and tolerances for engineer's parallels of Grade 2 shall be as given in Table 2.
- 5.3 Dimensional deviations for untoleranced dimensions shall be medium class according to IS 2102 (Part 1): 1980.
- 5.4 For sizes $25 \text{ mm} \times 50 \text{ mm} \times 250 \text{ mm}$ and above, suitable handles shall be provided.

Table 1 Dimensions and Tolerances for Engineer's Parallels (Grade 1)

(Clause 5.1)

All dimensions in millimetres.




Nominal Size		Permissible Errors for Individual Parallel		Parallelism of t and w	Functional Requirement for a Pair Matching		
t	w	l	Departure from Nominal t and w	Maximum Variation in t and w		of t and w (with in)	
5	10	100					
10	20	125	1.0.005	10:005	0:004	0.000	
15	30	150	±0·005	0.002	0.004	0.006	
20	40	200					
25	50	250					
30	60	300	±0 [.] 010	0.003	0.006	0.010	

Table 2 Dimensions and Tolerances for Engineer's Parallels (Grade 2)

(Clause 5.2)

All dimensions in millimetres.





Nominal Size		Permissible Errors for Individual Parallel		Parallelism of t and w	Functional Requirement for a Pair Matching		
t	w	1	Departure from Nominal t and w	Maximum Variation in t and w		of t and w (with in)	
5	10	100					
10	20	125	±0.010	0.004	0.008	0.012	
15	30	150	±0 010	0 004	0 505		
20	40	200					
25	50	250	1.0:030	0.006	0.015	0.050	
30	60	300	±0 [.] 020	0 000	0 012	0 020	
40	80	350	±0.052	0.002	0.014	0.020	
50	100	400	±0.030	0.008	0.016	0.022	

6 MATERIAL AND HARDNESS

- 6.1 The engineer's parallels of both grades shall be made of steel conforming to IS 7018 (Part 1): 1983.
- 6.2 Hardness for engineer's parallel shall be as given in IS 7018 (Part 1): 1983.

7 FINISH

- 7.1 The engineers' parallels shall be finished ground or preferably lapped on all four working sides.
- 7.2 All sharp edges shall be rounded off or chamfered to $1 \text{ mm} \times 45^{\circ} \text{ Max}$.

8 DESIGNATION

- 8.1 Engineer's parallel of Grade 1 of size 15 mm × 30 mm × 150 mm shall be designated as: Engineer's Parallel 15 × 30 × 150 Grade 1, IS 4241
- 8.2 Engineer's parallel of Grade 2 of size 40 mm × 80 mm × 350 mm shall be designated as:

 Engineer's Parallel 40 × 80 × 350 Grade 2, IS 4241

9 MARKING

- 9.1 Each engineer's parallel shall be marked legibly and permanently. Marking shall not protrude above the working surfaces of engineer's parallels. Each engineer's parallel shall be marked with following particulars:
 - a) Nominal size,
 - b) Grade,
 - c) Indication of source of manufacture, and
 - d) Number of this standard.

9.2 Standard Marking

The engineer's parallel may also be maked with Standard Mark, details of which may be obtained from Bureau of Indian Standards.

10 PRESERVATION AND PACKING

10.1 The engineer's parallels shall be protected against climatic conditions by suitable non-corrosive treatment and packed in a suitable protective box.

Standard Mark

The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

Bureau of Indian Standards

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc: No. LMD 05 (4923)

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected
	5.7	
	· ·	The state of the s

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan,	9	Bahadur	r Shah Zafar	Marg,	New Delhi 110002
Telephones : 33				-	

Telephones: 331 01 31, 331 13 75

Telegrams: Manaksanstha
(Common to all Offices)

Regional Offices:	Telephone	
Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	{331 01 31 331 13 7 5	
Eastern: 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola CALCUTTA 700054	37 86 62	
Northern: SCO 445-446, Sector 35-C, CHANDIGARH 160036	2 18 43	
Southern: C. I. T. Campus, IV Cross Road, MADRAS 600113	41 29 16	

Western: Manakalaya, E9 MIDC, Marol, Andheri (East) 6 32 92 95

Branches: AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE.

FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR.

PATNA. THIRUVANANTHAPURAM.

BOMBAY 400093